

TAURUS Premium SLE
DownLight Engine

DESCRIPTION:

Perfectly suitable to replace traditional lights
Perfect heat reduction technology
Wide voltage range
The narrow colour tolerance
Quick wiring
Strong spring mechanism
3 years warranty time.
Certificates: CE, ROHS

Indoor Recessed Application

High Efficiency Lighting and Automation Solutions



CRI
≥80

IP 20

3 years
WARRANTY

CO₂ ↓

LED
30.000
Hours

DRIVER
50.000
Hours

3000K
4000K
6500K

Article	Description	Lumen Output	System Power	Beam Angle	Body Color	Product Size	Package Qty.
404000008007***	DLS-001-0 TAURUS PREMIUM 3"	1340 Lm	11.6W	90°	White	ø100x70mm	20
404000008008***	DLS-001-0 TAURUS PREMIUM 4"	1560 Lm	13W	90°	White	ø115x80mm	20
404000008009***	DLS-001-0 TAURUS PREMIUM 5"	2300 Lm	19W	90°	White	ø161x100mm	10

Technical

High Efficient Constant Current Driver
Input Voltage: AC180-250V AC 50/60Hz
Power Factor: >0.95
LED Type: Mid-power chip with LM80
CRI: Ra≥80
Work temperature: -15°C+45°C
Material: Aluminum



Options

DALI, Touch-DIM, 1-10V, DSI control
Corridor Function application
Compatible Emergency Conversion Kit
CRI: Ra>90

LED Color Selection table

for WW 3000K, Pls. specify 030 at order.
for NW 4000K, Pls. specify 040 at order.
for CW 6500K, Pls. specify 065 at order.

Certificate



3": ø 85mm
4": ø 100mm
5": ø 140mm

Dimension

TECHNICAL NOTES:

Please contact us for different body colors or any special requests.
Please specify the colour temperatures of lighting, dotted the area in order.
Output lighting flux of LED lamp and power consumption of drivers may vary ± 5% because of the manufacturers values.