


**LOTUS Premium LLE** (Ceiling or Pendant)  
**LED Linear Light Engine**

**DESCRIPTION:**

Ultra thin design.  
 High efficient constant current driver.  
 Leading heat sink design.  
 No UV or infrared radiation, no danger of broken glass.  
 Low energy consumption, saves appr. 60% power comparing conventional light.  
 Be equipped with short circuit, overload protection.  
 3 years warranty time.  
 Certificates: CE, ROHs

Indoor Recessed Application

High Efficiency Lighting and Automation Solutions



| Article         | Description                      | Lumen Output | System Power | Beam Angle | Body Color | Product Size    | Package Qty. |
|-----------------|----------------------------------|--------------|--------------|------------|------------|-----------------|--------------|
| 401915003001*** | LLE-04-0 LOTUS PREMIUM L:900 mm  | ≥2960 Lm     | 25W          | 90°        | Grey       | L870*W74*H35mm  | 20           |
| 401915003004*** | LLE-04-0 LOTUS PREMIUM L:900 mm  | ≥4100 Lm     | 33W          | 90°        | Gray       | L870*W74*H35mm  | 20           |
| 401915003002*** | LLE-04-0 LOTUS PREMIUM L:1200 mm | ≥3870 Lm     | 33W          | 90°        | Gray       | L1150*W74*H35mm | 20           |
| 401915003003*** | LLE-04-0 LOTUS PREMIUM L:1200 mm | ≥5875 Lm     | 46W          | 90°        | Gray       | L1150*W74*H35mm | 20           |
| 401915003005*** | LLE-04-0 LOTUS PREMIUM L:1500 mm | ≥4200 Lm     | 36W          | 90°        | Gray       | L1470*W74*H35mm | 20           |
| 401915003006*** | LLE-04-0 LOTUS PREMIUM L:1500 mm | ≥8400 Lm     | 69W          | 90°        | Gray       | L1470*W74*H35mm | 20           |

**Technical**

Constant Current Driver with ENEC cetificate.  
 Input Voltage: AC 180-265V/AC 50/60Hz  
 Power Factor: >0.95  
 LED Type: SMD Chip with LM80 certificate  
 CRI: Ra≥80  
 Work temperature: -15°C ....+45°C  
 Material: Aluminum

**Options**

DALI, Touch-DIM, 1-10V, DSI control  
 Corridor Function application  
 Compatible Emergency Conversion Kit  
 Accessories: pendant equipment, mountain plate  
 Customised dimension


**LED Color Selection table**

for WW 3000K, Pls. specify 030 at order.  
 for NW 4000K, Pls. specify 040 at order.  
 for CW 6500K, Pls. specify 065 at order.

**Certificate**



**Dimension**



**TECHNICAL NOTES:**

Please contact us for different body colors or any special requests.  
 Please specify the colour temperatures of lighting, dotted the area in order.  
 Output of LED lighting flux current may vary ± 5%  
 Power consumption is approximately. Drivers and LED packets may vary according to the manufacturers value.

