LYRA Premium LLE (Ceiling or Pendant)

LED Linear Light Engine

DESCRIPTION:

Ultra thin design.
High efficient constant current driver.
Leading heat sink design.
No UV or infrared radiation, no danger of broken glass.
Low energy consumption, saves appr. 60% power comparing conventional light.
Be equipped with short circuit, overload protection.
3 years warranty time.
Certificates: CE, ROHs.

Indoor Recessed Application

High Effiency Lighting and Automation Solutions

CRI ≥80 | IP 20 | 3 years WARRANTY | CO_2 ↓ | LED 30.000 Hours | DRIVER 50.000 Hours | 3000K 4000K 6500K

Article	Description	Lumen Output	System Power	Beam Angle	Body Color	Product Size	Package Qty.
401915004001***	LLE-02-0 LYRA PREMIUM L:900 mm	≥2960 Lm	25W	90°	Grey	L870*W55*H75mm	20
401915004004***	LLE-02-0 LYRA PREMIUM L:900 mm	≥4100 Lm	33W	90°	Gray	L870*W55*H75mm	20
401915004002***	LLE-02-0 LYRA PREMIUM L:1200 mm	≥3870 Lm	33W	90°	Gray	L1150*W55*H75mm	20
401915004003***	LLE-02-0 LYRA PREMIUM L:1200 mm	≥5875 Lm	46W	90°	Gray	L1150*W55*H75mm	20
401915004005***	LLE-02-0 LYRA PREMIUM L:1500 mm	≥4200 Lm	36W	90°	Gray	L1462*W55*H75mm	20
401915004006***	LLE-02-0 LYRA PREMIUM L:1500 mm	≥8400 Lm	69W	90°	Gray	L1462*W55*H75mm	20

Technical

Constant Current Driver with ENEC cetificate.
Input Voltage: AC 180-265V/AC 50/60Hz
Power Factor: >0.95
LED Type: SMD Chip with LM80 certificate
CRI: Ra≥80
Work temperature: -15°C ....+45°C
Material: Aluminum

Options

DALI, Touch-DIM, 1-10V, DSI control
Corridor Function application
Compatible Emergency Conversion Kit
Accessories: pendant equipment, mountain plate
Customised dimension

LED Color Selection table

for WW 3000K, Pls. specify 030 at order.
for NW 4000K, Pls. specify 040 at order.
for CW 6500K, Pls. specify 065 at order.

Certificate

RoHS COMPLIANT

CE

Dimension



TECHNICAL NOTES:
Please contact us for different body colors or any special requests.
Please specify the colour temperatures of lighting, dotted the area in order.
Output of LED lighting flux current may vary ± 5%
Power consumption is approximately. Drivers and LED packets may vary according to the manufacturers value.

idalux®
for a bright future